



KerbCell

Description

Lock system in CorTen® steel or stainless steel. Mechanical parts made of 5 mm thick non-oxidizing steel. Closable for road salt.

Installation requirements

- Operating handle for opening and closing the lock.
- Anchor in concrete.
- Top side must be parallel to the sidewalk.
- The bottom of the opening lies a few millimeters below ground level for proper drainage.



Illustration	Type	Length	Height	Height above ground level	Width	kg/pcs	Number of locks	Material	Operating handle (incl.)
	WKC.L.3C	323 mm	250 mm	115 mm	195 mm	20 kg	3	CorTen	1
	WKC.L.3I	323 mm	250 mm	115 mm	195 mm	20 kg	3	RVS304	1
	WKC.L.5C	530 mm	250 mm	115 mm	195 mm	25 kg	5	CorTen	1
	WKC.L.5I	530 mm	250 mm	115 mm	195 mm	25 kg	5	RVS304	1
	WKC.F.3C	323 mm	165 mm	120 mm	545 mm	30 kg	3	CorTen	1
	WKC.F.3I	323 mm	165 mm	120 mm	545 mm	30 kg	3	RVS304	1
	WKC.F.5C	530 mm	165 mm	120 mm	545 mm	40 kg	5	CorTen	1
	WKC.F.5I	530 mm	165 mm	120 mm	545 mm	40 kg	5	RVS304	1

Accessories



Operating handle
WKB.H



wibio

Ambachtsstraat 11 - 2390 Malle - Belgium · t: +32 3 309 35 42 · e: hello@wibio.be · www.wibio.be
VAT BE 0869 824 932 · IBAN BE02 3200 7045 7840 · BIC/SWIFT BBRUBEBB