




Verge Edging

Description

Bespoke edging in blank (untreated) steel, CorTen® steel, galvanized steel or stainless steel. With clean top edge. Hidden connection. For both flexible and rigid designs.



Installation requirements

- Anchoring pins and connection plates included
- 2/3 of the profile must not exceed the surface area
- Compacted substrate or concrete for heavier traffic loads

Possible surfaces



● = Soft landscapes such as grass, soil, loose stones, sand, wood chips, peat

● = Rigid landscapes such as asphalt, concrete, rubber, gravel, gravelboard, plastic, bricks



Illustration	Type	Length	Height	Thickness	Material	Anchoring pins (incl.)	Connection plate (incl.)
	GVE.B	3000 mm	till 500 mm	3 to 12 mm	Blank	5	1
	GVE.G	3000 mm	till 500 mm	3 to 12 mm	Galvanized	5	1
	GVE.C	3000 mm	till 500 mm	3 to 12 mm	CorTen	5	1
	GVE.I	3000 mm	till 500 mm	3 to 12 mm	Stainless	5	1

In addition to this wide range of standard sizes, Verge Edging can be fully custom made, including rolling of curves and RAL coating. Please contact our Engineer Team.

Accessories

	Anchoring pins PEN.B.0450 / PEN.G.0450		Connection plate GVP		Internal corner Material & Thickness		External corner Material & Thickness
--	---	--	-------------------------	--	---	--	---

